

Application

This wall luminaire has a symmetric light distribution on one side and a wide spread light distribution on the other side. The symmetric light distribution can be used to illuminate façade and wall surfaces, with the installation surface also acting as the reflection surface. The wide spread light distribution can be used to illuminate ground surfaces along walls.

Materials

- Clear safety glass
- Marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy
- High temperature silicone gasket
- Mechanically captive stainless steel fasteners
- Silicone applied robotically to casting, plasma treated for increased adhesion
- Galvanized zinc-plated mounting bracket
- Pure anodized aluminum reflector

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 65

Weight: 11.0lbs.

Electrical

Operating voltage	120-277VAC
Minimum start temperature	-30° C
LED module wattage	33.7 W
System wattage	41.0 W
Controllability	0-10V dimmable
Color rendering index	Ra > 80
Luminaire lumens	4773lm
LED service life (L70)	60000hrs

LED color temperature

- ☐ 4000K (K4)
- ☐ 3500K (K35)
- ☐ 3000K (K3)
- ☐ 2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL, custom, and premium colors provided in polyester powder and/or liquid paint.

Available colors

- ☐ Black (BLK)
- ☐ Bronze (BRZ)
- ☐ Silver (SLV)
- ☐ White (WHT)
- ☐ Natural Bronze (NTB)
- ☐ RAL:
- ☐ CUS:

Type:


BEGA Product:

Project:

Modified:

Available options

- ☐ CUS
- Custom finish
- ☐ MGU
- Marine grade undercoat
- ☐ NTB
- Natural bronze (premium finish)
- ☐ RAL
- RAL Classic, matte finish



Wall washer · Symmetric upward · Lateral throw downward

	LED	A	B	C
B33393	33.7 W	9 ³ / ₄	6 ¹ / ₄	7 ³ / ₄

