

Application

The material thickness and strong crystal glass makes this impact-resistant luminaire extremely robust. Arranged individually or in groups, they are great design elements for a host of lighting applications.

Materials

Pressed crystal glass with white ceramic coating on one side
Marine grade, copper free (≤ 0.3% copper content) A360.0 aluminum alloy
High temperature silicone gasket
Mechanically captive stainless steel fasteners
Galvanized zinc-plated mounting bracket

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 65

Weight: 5.7 lbs.

Electrical

Operating voltage	120-277V AC
Minimum start temperature	-30° C
LED module wattage	4.7 W
System wattage	7.0 W
Controllability	0-10V dimmable
Color rendering index	Ra > 90
Luminaire lumens	505 lm
LED service life (L70)	60000 hrs

LED color temperature

- ☐ 4000K (K4)
- ☐ 3500K (K35)
- ☐ 3000K (K3)
- ☐ 2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL, custom, and premium colors provided in polyester powder and/or liquid paint.

Available colors

- | | |
|---|---------------------------------------|
| ☐ Black (BLK) | ☐ Bronze (BRZ) |
| ☐ Silver (SLV) | ☐ White (WHT) |
| ☐ Natural Bronze (NTB) | ☐ RAL: |
| ☐ CUS: | |

Type:


BEGA Product:

Project:

Modified:

Available options

- | | |
|---------------------------------|---------------------------------|
| ☐ CUS | Custom finish |
| ☐ DALI-2 | Enabled for DALI control system |
| ☐ FSC | Fusing |
| ☐ MGU | Marine grade undercoat |
| ☐ NTB | Natural bronze (premium finish) |
| ☐ RAL | RAL Classic, matte finish |



Impact-resistant wall luminaire · Partially shielded			
	LED	A	B
B33508	4.7 W	8 ³ / ₈	4 ¹ / ₂