

Application

The material thickness and strong crystal glass makes this impact-resistant luminaire extremely robust. Arranged individually or in groups, they are great design elements for a host of lighting applications.

Materials

Pressed crystal glass with white ceramic coating on one side
Marine grade, copper free (≤ 0.3% copper content) A360.0 aluminum alloy
High temperature silicone gasket
Mechanically captive stainless steel fasteners

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 65

Weight: 2.2 lbs.

Electrical

Operating voltage	120-277VAC
Minimum start temperature	-30° C
LED module wattage	2.8W
System wattage	6.6W
Controllability	0-10V dimmable
Color rendering index	Ra > 90
Luminaire lumens	323lm
LED service life (L70)	60000hrs

LED color temperature

- 4000K (K4)
- 3500K (K35)
- 3000K (K3)
- 2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL, custom, and premium colors provided in polyester powder and/or liquid paint.

Available colors

Black (BLK)	Bronze (BRZ)
Silver (SLV)	White (WHT)
Natural Bronze (NTB)	RAL:
CUS:	

Type:

BEGA Product:

Project:

Modified:

Available options

CUS	Custom finish
DALI-2	Enabled for DALI control system
FSC	Fusing
MGU	Marine grade undercoat
NTB	Natural bronze (premium finish)
RAL	RAL Classic, matte finish



Impact-resistant ceiling and wall luminaire · Unshielded				
		LED	A	B
B33534	ADA	2.8W	6 1/8	2 1/2