

Wall luminaire · Narrow beam upward · Narrow beam downward

BEGA

Application

Designed to provide general illumination and visual interest for interior and exterior locations. A narrow beam light distribution in both directions is ideal for general illumination of pathways and corridors, while highlighting various architectural features and creating patterns of light.

Materials

Clear safety glass
Marine grade, copper free ($\leq 0.3\%$ copper content) A360.0 aluminum alloy
High temperature silicone gasket
Mechanically captive stainless steel fasteners
Silicone applied robotically to casting, plasma treated for increased adhesion
Pure anodized aluminum reflector

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 64

Weight: 1.5 lbs.

Electrical

Operating voltage	120-277VAC
Minimum start temperature	-30° C
LED module wattage	3.8W
System wattage	7.3W
Controllability	0-10V dimmable
Color rendering index	Ra > 80
Luminaire lumens	294 lm
LED service life (L70)	60000 hrs

LED color temperature

4000K (K4)
3500K (K35)
3000K (K3)
2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL, custom, and premium colors provided in polyester powder and/or liquid paint.

Available colors

Black (BLK)	Bronze (BRZ)
Silver (SLV)	White (WHT)
Natural Bronze (NTB)	RAL:
CUS:	

Type:

BEGA Product:

Project:

Modified:

Available options

AMB	Amber LED
CUS	Custom finish
DALI-2	Enabled for DALI control system
FRO	Frosted lens
FSC	Fusing
MGU	Marine grade undercoat
NTB	Natural bronze (premium finish)
RAL	RAL Classic, matte finish
UPO	Uplight only



Wall luminaire · Narrow beam upward · Narrow beam downward

		LED	β	A	B	C
B33590	ADA	3.8 W	22°	3	5 1/8	3 3/4

BEGA 1000 BEGA Way, Carpinteria, CA 93013 (805) 684-0533 info@bega-us.com

Due to the dynamic nature of lighting products and the associated technologies, luminaire data on this sheet is subject to change at the discretion of BEGA North America. For the most current technical data, please refer to bega-us.com
© copyright BEGA 2026 Updated 08/21/26