

Application

Luminaires with direct and indirect light, to illuminate both the mounting surface and the desired space. Luminaires in this series are also available with an identical cover made of impact-resistant synthetic material for special applications, add P suffix to luminaire catalog number.

Materials

- Hand-blown three-ply opal glass
- Aluminum housing
- Fully potted waterstopper cable
- Galvanized zinc-plated mounting bracket

NRTL listed to North American Standards, for interior use only

Weight: 6.8 lbs.

Electrical

- | | |
|---------------------------|----------------|
| Operating voltage | 120-277VAC |
| Minimum start temperature | -30° C |
| LED module wattage | 16.4 W |
| System wattage | 19.3 W |
| Controllability | 0-10V dimmable |
| Color rendering index | Ra > 80 |
| Luminaire lumens | 1333 lm |
| LED service life (L70) | 60000 hrs |

LED color temperature

- 4000K (K4)
- 3500K (K35)
- 3000K (K3)
- 2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details


Finish

Select the desired material finish by using appropriate code number as suffix.

Available colors

- | | |
|------------|-------------|
| White (.1) | Silver (.2) |
|------------|-------------|

Type:
BEGA Product:
Project:
Modified:



Ceiling and wall luminaire · Opal glass · Direct/Indirect

		LED	A	B	C
B34278	ADA	16.4 W	14 1/4	3 3/8	10 1/2

