

Application

Ceiling and wall luminaires designed for the illumination of rooms, bathrooms, stairways, and other interior spaces characterized by their shallow projection featuring hand-blown, three-ply opal glass with satin matte finish.

Materials

Hand-blown opal glass  
Aluminum housing  
Galvanized zinc-plated mounting bracket

NRTL listed to North American Standards, for interior use only

Weight: 6.0 lbs.

Electrical

|                           |                          |
|---------------------------|--------------------------|
| Operating voltage         | 120-277V AC              |
| Minimum start temperature | -30° C                   |
| LED module wattage        | 25.9 W                   |
| System wattage            | 31.0 W                   |
| Controllability           | 0-10V dimming down to 1% |
| Color rendering index     | Ra > 90                  |
| Luminaire lumens          | 2312 lm                  |
| LED service life (L70)    | 60000 hrs                |

LED color temperature

4000K (K4)  
3500K (K35)  
3000K (K3)  
2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish


White finish. Custom colors not available.

Type:

BEGA Product:

Project:

Modified:



Ceiling and wall luminaire · Opal glass

|        |     | LED    | A                              | B                             | C                              |
|--------|-----|--------|--------------------------------|-------------------------------|--------------------------------|
| B34288 | ADA | 25.9 W | 15 <sup>3</sup> / <sub>8</sub> | 3 <sup>1</sup> / <sub>2</sub> | 11 <sup>7</sup> / <sub>8</sub> |

