

Application

Compact wall luminaires with light emission in two directions. Thick-walled brilliant crystal glass characterizes the design of these luminaires. Whether as single luminaires or aligned in rows, they illuminate and accentuate many features in the room.

Materials

Pressed crystal glass with white ceramic coating on one side
Marine grade, copper free (≤ 0.3% copper content) A360.0 aluminum alloy
Pure anodized aluminum reflector

NRTL listed to North American Standards, for interior use only

Weight: 2.2 lbs.

Electrical

Operating voltage	120, 220-240 OR 277 VAC
Minimum start temperature	-30° C
LED module wattage	7.6 W
System wattage	9.5 W
Controllability	0-10V dimmable
Color rendering index	Ra > 80
Luminaire lumens	542 lm
LED service life (L70)	60000 hrs

LED color temperature

- 4000K (K4)
- 3500K (K35)
- 3000K (K3)
- 2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

Select the desired material finish by using appropriate code number as suffix.

Available colors

- White (.1)
- Palladium (.4)
- Velvet black (.5)


Type:

BEGA Product:

Project:

Modified:

Included (available for pre-shipment)
B19538 Small opening wiring box



Wall luminaire · Light emission on two sides					
		LED	A	B	C
B50063	ADA	7.6 W	3 1/2	4 3/4	4

