

Application

Wall luminaires for a host of applications – arranged individually or in groups. An inner mechanism allows the glass to be swiveled in and out for re-lamping so they can also be installed horizontally or vertically in niches between walls.

Materials

Hand-blown three-ply opal glass
Aluminum housing

NRTL listed to North American Standards, for interior use only

Weight: 7.3 lbs.

Electrical

Operating voltage	120-277VAC
Minimum start temperature	-20° C
LED module wattage	23.6 W
System wattage	27.5 W
Controllability	0-10V dimming down to 0.1%
Color rendering index	Ra > 80
Luminaire lumens	2619lm
LED service life (L70)	60000hrs

LED color temperature

- ☐ 4000K (K4)
- ☐ 3500K (K35)
- ☐ 3000K (K3)
- ☐ 2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

Select the desired material finish by using appropriate code number as suffix.

Available colors

- ☐ Stainless steel (.2)
- ☐ Chrome (.3)

Type:

BEGA Product:

Project:

Modified:

Available options

- ☐ DALI-2 Enabled for DALI control system

Included (available for pre-shipment)

- ☐ B19537 Narrow opening wiring box



Linear wall luminaire · Opal glass				
	LED	A	B	C
B50069	23.6 W	27 3/4	3 1/8	4 1/2

