

Application

Our LED technology and state-of-the-art manufacturing processes allow us to create these exceptionally shallow luminaire designs. Thick walled crystal glass completes the design and gives them their distinctive character.

Materials

Pressed crystal glass with white ceramic coating on one side
Die-cast zinc housing

NRTL listed to North American Standards, for interior use only

Weight: 2.9 lbs.

Electrical

Operating voltage	120-277V AC
Minimum start temperature	-30° C
LED module wattage	12.2 W
System wattage	15.6 W
Controllability	0-10V, TRIAC, and ELV dimmable
Color rendering index	Ra > 80
Luminaire lumens	782 lm
LED service life (L70)	60000 hrs

LED color temperature

- ☐ 4000K (K4)
- ☐ 3500K (K35)
- ☐ 3000K (K3)
- ☐ 2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details


Finish

Select the desired material finish by using appropriate code number as suffix.

Available colors

- ☐ White (.1)
- ☐ Stainless steel (.2)
- ☐ Chrome (.3)

Type:
BEGA Product:
Project:
Modified:



Wall luminaire · Light emission on two sides					
		LED	A	B	C
B50072	ADA	12.2 W	6 7 / ₈	4 1 / ₂	2 1 / ₈

