

Application
Ceiling and wall luminaires designed for general purpose illumination for interior locations featuring a shallow depth and hand-blown, three-ply opal glass with satin matte finish.

Materials
Hand-blown opal glass
Aluminum housing
Galvanized zinc-plated mounting bracket

NRTL listed to North American Standards, for interior use only

Weight: 4.6 lbs.

Electrical
Operating voltage 120-277VAC
Minimum start temperature -30° C
LED module wattage 25.9 W
System wattage 31.2 W
Controllability 0-10V dimming down to 1%
Color rendering index Ra > 80
Luminaire lumens 2479 lm
LED service life (L70) 60000 hrs

LED color temperature
4000K (K4)
3500K (K35)
3000K (K3)
2700K (K27)


BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish
White finish. Custom colors not available.

Type:
BEGA Product:
Project:
Modified:

Available accessories
B13079 Trim ring · White
B13080 Trim ring · Stainless steel
B13081 Trim ring · Chrome

See individual accessory spec sheet for details.



Ceiling and wall luminaire · Opal glass				
		LED	A	B
B50079	ADA	25.9 W	13 ³ / ₈	3 ¹ / ₂

