

**Application**  
Ceiling and wall luminaires designed for general purpose illumination for interior locations featuring a shallow depth and hand-blown, three-ply opal glass with satin matte finish.

**Materials**  
Hand-blown opal glass  
Aluminum housing  
Galvanized zinc-plated mounting bracket

NRTL listed to North American Standards, for interior use only

**Weight:** 8.6 lbs.

**Electrical**  
Operating voltage                    120-277VAC  
Minimum start temperature       -30° C  
LED module wattage                37.8 W  
System wattage                      43.0 W  
Controllability                      0-10V dimming down to 1%  
Color rendering index              Ra > 80  
Luminaire lumens                    3451 lm  
LED service life (L70)              60000 hrs

**LED color temperature**  
4000K (K4)  
3500K (K35)  
3000K (K3)  
2700K (K27)


BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

**Finish**  
White finish. Custom colors not available.

Type:  
BEGA Product:  
Project:  
Modified:

**Available accessories**  
B13082      Trim ring · White  
B13083      Trim ring · Stainless steel  
B13084      Trim ring · Chrome

See individual accessory spec sheet for details.



| Ceiling and wall luminaire · Opal glass |     |        |        |   |
|-----------------------------------------|-----|--------|--------|---|
|                                         |     | LED    | A      | B |
| B50080                                  | ADA | 37.8 W | 15 1/2 | 4 |

