

Application

Open wall luminaires with a high level of efficiency, characterized by an elongated design. As solid and reliable lighting tools with modern lamp technology and high-quality workmanship, they will provide very cost-effective service over long operating periods.

Materials

Hand-blown three-ply opal glass
Aluminum housing

NRTL listed to North American Standards, for interior use only

Weight: 7.9 lbs.

Electrical

Operating voltage	120-277VAC
Minimum start temperature	-20° C
LED module wattage	36.4 W
System wattage	42.0 W
Controllability	0-10V dimming down to 0.1%
Color rendering index	Ra > 80
Luminaire lumens	4498 lm
LED service life (L70)	60000 hrs

LED color temperature

- 4000K (K4)
- 3500K (K35)
- 3000K (K3)
- 2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

White finish. Custom colors not available.

Type:

BEGA Product:

Project:

Modified:

Available options

- DALI-2 Enabled for DALI control system

Included (available for pre-shipment)

- B19537 Narrow opening wiring box



Linear wall luminaire · Opal glass				
	LED	A	B	C
B50085	36.4 W	4 ³ / ₈	27 ⁷ / ₈	5 ³ / ₄

