

Application

Semi-recessed luminaires with broad spread light distribution. The distinctive hand-blown, three-ply opal glass with concave interior surface provides a soft uniform light gradient.

Materials

- Hand-blown three-ply opal glass
- Marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy
- Stainless steel screw clamps
- Aluminum ceiling mounted driver box

NRTL listed to North American Standards, for interior use only

Weight: 5.5 lbs.

Electrical


- Operating voltage120-277V AC
- Minimum start temperature-20° C
- LED module wattage37.5 W
- System wattage44.0 W
- Controllability0-10V dimming down to 0.1%
- Color rendering indexRa > 90
- Luminaire lumens3456 lm
- LED service life (L70)60000 hrs

LED color temperature

- 4000K (K4)
- 3500K (K35)
- 3000K (K3)
- 2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Type:
BEGA Product:
Project:
Modified:



- Available options
- CP50177- 120V Ceiling pan (0-10V dimming down to 0.1%)
 - CP50177- 277V Ceiling pan (0-10V dimming down to 0.1%)



Semi-recessed ceiling luminaire · Opal glass				
	LED	A	B	C
B50177	37.5 W	10 ³ / ₈	3	2 ³ / ₈