

Application

A versatile family of luminaires, the symmetric light distribution version is designed to wash wall surfaces. These luminaires are an excellent lighting tool for efficient, indirect illumination of interior spaces.

Materials

Clear safety glass
Marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy
Pure anodized aluminum reflector surface

NRTL listed to North American Standards, for interior use only

Weight: 3.7 lbs.

Electrical

Operating voltage	120-277VAC
Minimum start temperature	-30° C
LED module wattage	16.5 W
System wattage	19.2 W
Controllability	0-10V, TRIAC, and ELV dimmable
Color rendering index	Ra > 90
Luminaire lumens	1585 lm
LED service life (L70)	60000 hrs

LED color temperature

- 4000K (K4)
- 3500K (K35)
- 3000K (K3)
- 2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details


Finish

Select the desired material finish by using appropriate code number as suffix.

Available colors

- White (.1)
- Palladium (.4)
- Velvet black (.5)

Type:
BEGA Product:
Project:
Modified:



Wall washer · Symmetric				
	LED	A	B	C
B50198	16.5 W	10 1/4	3	6 1/8

