

Application

The pendant luminaire downlight satisfies the designers wish when it comes to creating a comfortable interior space. The downlight component provides efficient task lighting for floor or table surfaces, while the opal glass cylinder glows to create ambient lighting.

Materials

Hand-blown opal glass  
Hand-blown crystal glass  
Marine grade, copper free (≤ 0.3% copper content) A360.0 aluminum alloy  
Pure anodized aluminum reflector

NRTL listed to North American Standards, for interior use only

Weight: 15.0lbs.

Electrical

|                           |                            |
|---------------------------|----------------------------|
| Operating voltage         | 120-277VAC                 |
| Minimum start temperature | -20° C                     |
| LED module wattage        | 44.2 W                     |
| System wattage            | 52.0 W                     |
| Controllability           | 0-10V dimming down to 0.1% |
| Color rendering index     | Ra > 90                    |
| Luminaire lumens          | 5085 lm                    |
| LED service life (L70)    | 60000 hrs                  |

LED color temperature

4000K (K4)  
3500K (K35)  
3000K (K3)  
2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

White finish. Custom colors not available.

Type:

BEGA Product:

Project:

Modified:



| Pendant · Opal glass · Direct |        |       |    |     |
|-------------------------------|--------|-------|----|-----|
|                               | LED    | A     | B  | C   |
| B50236                        | 44.2 W | 7 3/8 | 19 | 236 |

