

Application

LED technology and our own LED module production facilities enable us to pursue new avenues of luminaire design and to develop distinctive luminaires in special sizes. This seamless design presents new and creative options in many areas of interior design.

Materials

White UV-stabilized acrylic diffuser
Aluminum housing
Stainless steel suspension cable

NRTL listed to North American Standards, for interior use only

Weight: 14.3lbs.

Electrical

Operating voltage 120-277V AC
Minimum start temperature -20° C
LED module wattage 100.0W
System wattage 116.0W
Controllability 0-10V dimming down to 0.1%
Color rendering index Ra > 90
Luminaire lumens 12924 lm
LED service life (L70) 60000 hrs

LED color temperature

4000K (K4)
3500K (K35)
3000K (K3)
2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

Select the desired material finish by using appropriate code number as suffix.

Available colors

White (.1) Matte aluminum (.2)

Type:

BEGA Product:

Project:

Modified:

Available options

DALI-2 Enabled for DALI control system



LINEARA · LINEARA				
	LED	A	B	C
B50401	100.0W	79 ⁵ / ₈	3 ¹ / ₈	78 ³ / ₄

