

Application

This luminaire is designed to illuminate rooms, stairways, or hallways while creating an intriguing contrast between the luminaire and the mounting surface. The hand-blown, three-ply opal glass distributes diffuse light uniformly throughout a space.

Materials

- Hand-blown opal glass
- Aluminum housing
- Stainless steel screw clamps
- Aluminum ceiling mounted driver box

NRTL listed to North American Standards, for interior use only

Weight: 2.1 lbs.

Electrical

- | | |
|---------------------------|----------------------------|
| Operating voltage | 120-277VAC |
| Minimum start temperature | -20° C |
| LED module wattage | 8.4 W |
| System wattage | 12.0 W |
| Controllability | 0-10V dimming down to 0.1% |
| Color rendering index | Ra > 90 |
| Luminaire lumens | 570lm |
| LED service life (L70) | 60000hrs |

LED color temperature

- 4000K (K4)
- 3500K (K35)
- 3000K (K3)
- 2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

Select the desired trim ring material finish by using appropriate code number as suffix.

Available colors

- | | |
|------------|----------------------|
| White (.1) | Stainless steel (.2) |
|------------|----------------------|

Type:


BEGA Product:

Project:

Modified:

Available options

- | | |
|---------|---|
| CP50523 | Ceiling Pan (0-10V dimmable down to 0.1%) |
|---------|---|



Recessed ceiling luminaire · Opal glass				
		LED	A	B
B50523	ADA	8.4 W	7 ¹ / ₈	2 ³ / ₈

