

Application

This luminaire is designed to illuminate rooms, stairways, or hallways while creating an intriguing contrast between the luminaire and the mounting surface. The hand-blown, three-ply opal glass distributes diffuse light uniformly throughout a space.

Materials

- Hand-blown opal glass
- Aluminum housing
- Stainless steel screw clamps
- Aluminum ceiling mounted driver box

NRTL listed to North American Standards, for interior use only

Weight: 7.3 lbs.

Electrical

- Operating voltage120-277VAC
- Minimum start temperature-20° C
- LED module wattage17.8 W
- System wattage23.0 W
- Controllability0-10V dimming down to 0.1 %
- Color rendering indexRa > 90
- Luminaire lumens1651 lm
- LED service life (L70)60000 hrs

LED color temperature

- 4000K (K4)
- 3500K (K35)
- 3000K (K3)
- 2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

Select the desired trim ring material finish by using appropriate code number as suffix.

Available colors

- White (.1)
- Stainless steel (.2)

Type:


BEGA Product:

Project:

Modified:

Available options

- CP12121 Ceiling Pan (0-10V dimmable down to 0.1 %)



Recessed ceiling luminaire · Opal glass				
		LED	A	B
B50524	ADA	17.8 W	10	2 3⁄8

