

Application

This luminaire is designed to illuminate rooms, stairways, or hallways while creating an intriguing contrast between the luminaire and the mounting surface. The hand-blown, three-ply opal glass distributes diffuse light uniformly throughout a space.

Materials

- Hand-blown opal glass
- Aluminum housing
- Stainless steel screw clamps
- Aluminum ceiling mounted driver box

NRTL listed to North American Standards, for interior use only

Weight: 8.4 lbs.

Electrical

- Operating voltage120-277VAC
- Minimum start temperature-20° C
- LED module wattage43.7 W
- System wattage50.0 W
- Controllability0-10V dimming down to 0.1%
- Color rendering indexRa > 90
- Luminaire lumens3066 lm
- LED service life (L70)60000 hrs

LED color temperature

- 4000K (K4)
- 3500K (K35)
- 3000K (K3)
- 2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

Select the desired trim ring material finish by using appropriate code number as suffix.

Available colors

- White (.1)
- Stainless steel (.2)

Type:


BEGA Product:

Project:

Modified:

Available options

- CP50526-120V Ceiling pan - 120V Only (0-10V dimmable down to 0.1%)
- CP50526-277V Ceiling pan - 277V Only (0-10V dimmable down to 0.1%)



Recessed ceiling luminaire · Opal glass

		LED	A	B
B50526	ADA	43.7 W	16 ⁷ / ₈	2 ³ / ₈

