

Application

Hand-blown, three-ply opal glass covers the recessed opening and, despite its very shallow projection, illuminates the room and mounting surface uniformly. The lateral illumination on the finished surface produces a floating effect.

Materials

Hand-blown opal glass  
Aluminum housing  
Stainless steel screw clamps  
Aluminum ceiling mounted driver box

NRTL listed to North American Standards, for interior use only

Weight: 10.4 lbs.

Electrical

|                           |                            |
|---------------------------|----------------------------|
| Operating voltage         | 120-277VAC                 |
| Minimum start temperature | -20° C                     |
| LED module wattage        | 43.7 W                     |
| System wattage            | 50.0 W                     |
| Controllability           | 0-10V dimming down to 0.1% |
| Color rendering index     | Ra > 90                    |
| Luminaire lumens          | 3200 lm                    |
| LED service life (L70)    | 60000 hrs                  |

LED color temperature

4000K (K4)  
3500K (K35)  
3000K (K3)  
2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Type:


BEGA Product:

Project:

Modified:

Available options

|              |                                                       |
|--------------|-------------------------------------------------------|
| CP50526-120V | Ceiling pan - 120V Only (0-10V dimmable down to 0.1%) |
| CP50526-277V | Ceiling pan - 277V Only (0-10V dimmable down to 0.1%) |



| Semi-recessed ceiling and wall luminaire · Opal glass |     |        |                                |                               |
|-------------------------------------------------------|-----|--------|--------------------------------|-------------------------------|
|                                                       |     | LED    | A                              | B                             |
| B50530                                                | ADA | 43.7 W | 17 <sup>1</sup> / <sub>8</sub> | 2 <sup>3</sup> / <sub>8</sub> |

BEGA 1000 BEGA Way, Carpinteria, CA 93013 (805) 684-0533 info@bega-us.com

Due to the dynamic nature of lighting products and the associated technologies, luminaire data on this sheet is subject to change at the discretion of BEGA North America. For the most current technical data, please refer to bega-us.com  
© copyright BEGA 2025 Updated 09/12/25