

Application

The thick-walled crystal glass of this downlight brings sparkle and added interest to any ceiling surface, while the inner frosted section provides glare control and minimizes the direct view of the LED source. The compact, shallow housing is ideal for areas with low ceiling heights such as lobbies and corridors.

Materials

- Partially frosted pressed crystal glass
- Aluminum housing
- Galvanized zinc-plated mounting bracket
- Pure anodized aluminum reflector surface

NRTL listed to North American Standards, for interior use only

Weight: 2.6 lbs.

Electrical

Operating voltage	120-277V AC
Minimum start temperature	-30° C
LED module wattage	11.5 W
System wattage	14.0 W
Controllability	0-10V, TRIAC, and ELV dimmable
Color rendering index	Ra > 90
Luminaire lumens	1409 lm
LED service life (L70)	60000 hrs

LED color temperature

- 4000K (K4)
- 3500K (K35)
- 3000K (K3)
- 2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

Select the desired material finish by using appropriate code number as suffix.

Available colors


- White (.1)
- Stainless steel (.2)

Type:

BEGA Product:

Project:

Modified:



Ceiling luminaire · Crystal glass			
	LED	A	B
B50568	11.5 W	5 ³ / ₈	3 ¹ / ₈