

Application

This recessed downlight's unique beauty and versatility is enhanced by the choice of four matte interior finishes combined with a white trim finish. These finishes may be chosen to complement a wide array of interior spaces. A subtle hint of colored light on the outside edge of the beam spread results from the internally reflected light. The result is an eye-catching and elegant lighting effect.

Materials

Clear UV-stabilized acrylic diffuser
Marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy
NRTL listed to North American Standards, for interior use only

Weight: 1.2 lbs.

Electrical

Operating voltage	120-277VAC
Minimum start temperature	-20° C
LED module wattage	17.6W
System wattage	21.0W
Controllability	0-10V dimming down to 0.1%
Color rendering index	Ra > 90
Luminaire lumens	1481 lm
LED service life (L70)	60000hrs

LED color temperature

- 4000K (K4)
- 3500K (K35)
- 3000K (K3)
- 2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

Select the desired interior finish by using appropriate code number as suffix.

Available colors

- | | |
|------------------|---------------------|
| White (.1) | Matte aluminum (.2) |
| Matte brass (.4) | Matte copper (.6) |

Type:


BEGA Product:

Project:

Modified:

Available options

- | | |
|--------------|---|
| CP50577-120V | Ceiling pan - 120V only (0-10V dimmable down to 0.1%) |
| CP50577-277V | Ceiling pan - 277V only (0-10V dimmable down to 0.1%) |



Downlight · STUDIO LINE · White				
	LED	β	A	B
B50579	17.6W	69°	5 ⁷ / ₈	3 ³ / ₈

