

Application

A decorative semi-recessed downlight, designed for a diverse range of applications. The luminaire includes thick-walled crystal glass that provides sparkle and added interest to any ceiling surface, while the inner frosted section provides glare control and minimizes the direct view of the LED source. Designed with a very small aperture, this luminaire is ideal for both new and retrofit construction.

Materials

Partially frosted pressed crystal glass
Marine grade, copper free (≤ 0.3% copper content) A360.0 aluminum alloy
Stainless steel screw clamps
Aluminum ceiling mounted driver box
Pure anodized aluminum reflector

NRTL listed to North American Standards, for interior use only

Weight: 0.9 lbs.

Electrical

Operating voltage	120-277V AC
Minimum start temperature	-30° C
LED module wattage	8.5W
System wattage	12.0W
Controllability	0-10V, TRIAC, and ELV dimmable
Color rendering index	Ra > 90
Luminaire lumens	580lm
LED service life (L70)	60000 hrs

LED color temperature

4000K (K4)
3500K (K35)
3000K (K3)
2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Type:


BEGA Product:

Project:

Modified:

Available options

CP50711 Ceiling Pan (0-10V dimming only down to 0.1%)



Semi-recessed downlight · Partially frosted crystal glass			
	LED	A	B
B50593	8.5W	3 1/8	1 7/8