

Application

This pendent features thick-walled crystal glass, adding sparkle and visual interest to a room while the inner frosted section provides glare control and minimizes direct view of the LED source.

Materials

Partially frosted pressed crystal glass  
Marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy  
Galvanized zinc-plated mounting bracket  
Pure anodized aluminum reflector surface  
Silicone optic with excellent high temperature and UV stability

NRTL listed to North American Standards, for interior use only

Weight: 5.3 lbs.

Electrical

|                           |                                |
|---------------------------|--------------------------------|
| Operating voltage         | 120-277VAC                     |
| Minimum start temperature | -30° C                         |
| LED module wattage        | 11.5 W                         |
| System wattage            | 14.0 W                         |
| Controllability           | 0-10V, TRIAC, and ELV dimmable |
| Color rendering index     | Ra > 90                        |
| Luminaire lumens          | 1170 lm                        |
| LED service life (L70)    | 60000 hrs                      |

LED color temperature

- ☐ 4000K (K4)
- ☐ 3500K (K35)
- ☐ 3000K (K3)
- ☐ 2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

Select the desired material finish by using appropriate code number as suffix.

Available colors

- |                                     |                                               |
|-------------------------------------|-----------------------------------------------|
| <input type="checkbox"/> White (.1) | <input type="checkbox"/> Stainless steel (.2) |
|-------------------------------------|-----------------------------------------------|

Type:

BEGA Product:

Project:

Modified:



Pendant luminaire · Crystal glass

|        | LED    | A                             | B                             | C   |
|--------|--------|-------------------------------|-------------------------------|-----|
| B50613 | 11.5 W | 5 <sup>3</sup> / <sub>8</sub> | 5 <sup>3</sup> / <sub>4</sub> | 120 |

