

Application

This pendent features thick-walled crystal glass, adding sparkle and visual interest to a room while the inner frosted section provides glare control and minimizes direct view of the LED source.

Materials

Partially frosted pressed crystal glass
Marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy
Galvanized zinc-plated mounting bracket
Pure anodized aluminum reflector surface
Silicone optic with excellent high temperature and UV stability

NRTL listed to North American Standards, for interior use only

Weight: 6.8lbs.

Electrical

Operating voltage	120-277VAC
Minimum start temperature	-30° C
LED module wattage	17.0W
System wattage	21.0W
Controllability	0-10V, TRIAC, and ELV dimmable
Color rendering index	Ra > 90
Luminaire lumens	1682lm
LED service life (L70)	60000hrs

LED color temperature

- ☐ 4000K (K4)
- ☐ 3500K (K35)
- ☐ 3000K (K3)
- ☐ 2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

Select the desired material finish by using appropriate code number as suffix.

Available colors


- | | |
|-------------------------------------|---|
| ☐ White (.1) | ☐ Stainless steel (.2) |
|-------------------------------------|---|

Type:

BEGA Product:

Project:

Modified:



Pendant luminaire · Crystal glass				
	LED	A	B	C
B50614	17.0W	7	6 ⁷ / ₈	120

