

Application

This compact luminaire is characterized by high light output and minimal recessed depth. The trimless, thick-walled crystal glass brings sparkle and added interest to any ceiling surface, while the inner frosted sections provide glare control.

Materials

- Partially frosted pressed crystal glass
- Marine grade, copper free (≤ 0.3% copper content) A360.0 aluminum alloy
- Aluminum ceiling mounted driver box
- Pure anodized aluminum reflector surface
- Silicone optic with excellent high temperature and UV stability

NRTL listed to North American Standards, for interior use only

Weight: 2.9 lbs.

Electrical


- Operating voltage120-277V AC
- Minimum start temperature-20° C
- LED module wattage8.1 W
- System wattage12.0 W
- Controllability0-10V dimming down to 0.1%
- Color rendering indexRa > 90
- Luminaire lumens809 lm
- LED service life (L70)60000 hrs

LED color temperature

- 4000K (K4)
- 3500K (K35)
- 3000K (K3)
- 2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Type:
BEGA Product:
Project:
Modified:



Available options
CP50374 Ceiling pan (0–10V dimming only)



Semi-recessed downlight · Crystal glass				
	LED	β	A	B
B50687	8.1 W	59°	5 3⁄₄	3 1⁄₂