

Application

Accent luminaires for the private home and garden. These unshielded luminaires create a pleasant light effect and are provided with an earth spike for flexible installation as design parameters change over time. Low voltage magnetic transformer required for operation.

Materials

Hand-blown three-ply opal glass
High temperature silicone gasket
Composite installation housing

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 65

Weight: 2.2 lbs.

Electrical

Operating voltage	12VAC
Minimum start temperature	-40° C
LED module wattage	1.9W
System wattage	2.5W
Controllability	Non-Dimming
Color rendering index	Ra > 80
Luminaire lumens	135lm
LED service life (L70)	60000hrs

LED color temperature

- 4000K (K4)
- 3500K (K35)
- 3000K (K3)
- 2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

Synthetic housing provided in standard BEGA Graphite. Custom colors not available.

Type:

BEGA Product:

Project:

Modified:


Available options

- | | |
|-----|-----------|
| AMB | Amber LED |
| FSC | Fusing |

Available accessories

- B536 Low voltage magnetic transformer · 300W

See individual accessory spec sheet for details.



Garden luminaire with earth spike · Unshielded · 12V AC				
	LED	A	B	C
B55005	1.9W	2 ⁵ / ₈	10 ³ / ₄	7 ⁵ / ₈

