

Application

Accent luminaires for the private home and garden. These unshielded luminaires create a pleasant light effect and are provided with an earth spike for flexible installation as design parameters change over time. Low voltage magnetic transformer required for operation.

Materials

Hand-blown three-ply opal glass
High temperature silicone gasket
Composite installation housing

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 65

Weight: 2.6 lbs.

Electrical

Operating voltage	12VAC
Minimum start temperature	-40° C
LED module wattage	1.9W
System wattage	2.5W
Controllability	Non-Dimming
Color rendering index	Ra > 80
Luminaire lumens	245lm
LED service life (L70)	60000hrs

LED color temperature

- ☐ 4000K (K4)
- ☐ 3500K (K35)
- ☐ 3000K (K3)
- ☐ 2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

Synthetic housing provided in standard BEGA Graphite. Custom colors not available.

Type:

BEGA Product:

Project:

Modified:


Available options

- ☐ AMB Amber LED

Available accessories

- ☐ B536 Low voltage magnetic transformer · 300W

See individual accessory spec sheet for details.



Garden luminaire with earth spike · Unshielded · 12V AC

	LED	A	B	C
B55030	1.9W	5 ⁷ / ₈	10 ¹ / ₈	7 ⁵ / ₈

