

Application
Ceiling and wall luminaire designed for general purpose illumination featuring three-ply opal glass. This luminaire can be utilized individually or in groups for glare-free illumination in interior and exterior spaces.

Materials
Three-ply opal glass
Die-cast aluminum
High temperature silicone gasket

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 65

Weight: 3.1 lbs.

Electrical
Operating voltage 120-277V AC
Minimum start temperature -30° C
LED module wattage 3.0 W
System wattage 4.0 W
Controllability 0-10V dimmable
Color rendering index Ra > 90
Luminaire lumens 300 lm
LED service life (L70) 60000 hrs

LED color temperature
☐ 4000K (K4)
☐ 3500K (K35)
☐ 3000K (K3)
☐ 2700K (K27)


BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish
All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL, custom, and premium colors provided in polyester powder and/or liquid paint.

Available colors
☐ Black (BLK) ☐ Bronze (BRZ)
☐ Silver (SLV) ☐ White (WHT)
☐ Natural Bronze (NTB) ☐ RAL:
☐ CUS:

Type:
BEGA Product:
Project:
Modified:

Available options
☐ CUS Custom finish
☐ DALI-2 Enabled for DALI control system
☐ MGU Marine grade undercoat
☐ NTB Natural bronze (premium finish)
☐ RAL RAL Classic, matte finish



Ceiling and wall luminaire · Opal glass				
		LED	A	B
B55115	ADA	3.0 W	9 ¹ / ₂	3 ³ / ₈

