

Application

Ceiling and wall luminaire designed for general purpose illumination featuring three-ply opal glass. This luminaire can be utilized individually or in groups for glare-free illumination in interior and exterior spaces.

Materials

Three-ply opal glass
Die-cast aluminum
High temperature silicone gasket

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 65

Weight: 4.0 lbs.

Electrical

Operating voltage	120-277V AC
Minimum start temperature	-40° C
LED module wattage	8.4 W
System wattage	10.0 W
Controllability	0-10V dimmable
Color rendering index	Ra > 90
Luminaire lumens	688 lm
LED service life (L70)	60000 hrs

LED color temperature

4000K (K4)
3500K (K35)
3000K (K3)
2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL, custom, and premium colors provided in polyester powder and/or liquid paint.

Available colors

Black (BLK)	Bronze (BRZ)
Silver (SLV)	White (WHT)
Natural Bronze (NTB)	RAL:
CUS:	

Type:


BEGA Product:

Project:

Modified:

Available options

CUS	Custom finish
FSC	Fusing
MGU	Marine grade undercoat
NTB	Natural bronze (premium finish)
RAL	RAL Classic, matte finish



Ceiling and wall luminaire · Opal glass

	LED	A	B
B55116	8.4 W	11	4 1/8

