

Application

Designed for down lighting atriums, canopies, passages, and other interior and exterior locations featuring a symmetric narrow beam distribution.

Materials

- Clear safety glass
- Marine grade, copper free ($\leq 0.3\%$ copper content) A360.0 aluminum alloy
- 316 grade stainless steel
- Stainless steel screw clamps
- High temperature silicone gasket
- Pure anodized aluminum reflector

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 65

Weight: 1.4 lbs.

Electrical

LED module wattage	12.7 W
System wattage	15.5 W
Color rendering index	Ra > 80
Luminaire lumens	1161 lm
LED service life (L70)	60000 hrs

LED color temperature

- ☐ 4000K (K4)
- ☐ 3500K (K35)
- ☐ 3000K (K3)
- ☐ 2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

#4 brushed stainless steel. Custom colors are not available.

Type:

BEGA Product:

Project:


Modified:

Available options

- ☐ DALI-2 Enabled for DALI control system
- ☐ FRO Frosted lens
- ☐ FSC Fusing
- ☐ HXL Hex cell louver
- ☐ SLL Solite lens

Included (available for pre-shipment)

- ☐ CP5925 Ceiling pan



Downlight · Narrow beam					
	LED	β	A	B	C
B55825	12.7 W	17°	6 ³ / ₈	3 ¹ / ₄	18

