

Application

Designed for down lighting atriums, canopies, passages, and other interior and exterior locations featuring a symmetric narrow beam light distribution.

Materials

Clear safety glass
Marine grade, copper free ($\leq 0.3\%$ copper content) A360.0 aluminum alloy
High temperature silicone gasket
Stainless steel screw clamps
Pure anodized aluminum reflector

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 65

Weight: 0.9 lbs.

Electrical

LED module wattage	8.7 W
System wattage	11.0 W
Color rendering index	Ra > 80
Luminaire lumens	921 lm
LED service life (L70)	60000 hrs

LED color temperature

- ☐ 4000K (K4)
- ☐ 3500K (K35)
- ☐ 3000K (K3)
- ☐ 2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL, custom, and premium colors provided in polyester powder and/or liquid paint.

Available colors

- | | |
|---|---------------------------------------|
| ☐ Black (BLK) | ☐ Bronze (BRZ) |
| ☐ Silver (SLV) | ☐ White (WHT) |
| ☐ Natural Bronze (NTB) | ☐ RAL: |
| ☐ CUS: | |

Type:

BEGA Product:

Project:


Modified:

Available options

- | | |
|------------------------------------|---------------------------|
| ☐ 347V | 347V input |
| ☐ AMB 55923 | Amber LED |
| ☐ CUS | Custom finish |
| ☐ FRO | Frosted lens |
| ☐ FSC | Fusing |
| ☐ HXL | Hex cell louver |
| ☐ MGU | Marine grade undercoat |
| ☐ RAL | RAL Classic, matte finish |
| ☐ SLL | Solite lens |

Included (available for pre-shipment)

- | | |
|---------------------------------|-------------|
| ☐ CP5923 | Ceiling pan |
|---------------------------------|-------------|



Downlight · Narrow beam					
	LED	β	A	B	C
B55923	8.7 W	19°	4 ³ / ₈	3 ¹ / ₄	18