

Application

A compact ceiling mounted downlight with partially frosted crystal glass. The partially frosted crystal glass creates an additional vertical light component that supplements the downlight. These luminaires are designed for down lighting atriums, canopies, passages, and other interior and exterior locations.

Materials

Partially frosted pressed crystal glass
Marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy
High temperature silicone gasket
Pure anodized aluminum reflector

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 65

Weight: 1.3 lbs.

Electrical

Operating voltage	120-277VAC
Minimum start temperature	-30° C
LED module wattage	3.0W
System wattage	7.0W
Controllability	0-10V dimmable
Color rendering index	Ra > 90
Luminaire lumens	301 lm
LED service life (L70)	60000 hrs

LED color temperature

- ☐ 4000K (K4)
- ☐ 3500K (K35)
- ☐ 3000K (K3)
- ☐ 2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL, custom, and premium colors provided in polyester powder and/or liquid paint.

Available colors

- | | |
|---------------------------------------|---------------------------------------|
| ☐ Black (BLK) | ☐ Bronze (BRZ) |
| ☐ Silver (SLV) | ☐ White (WHT) |
| ☐ RAL: | ☐ CUS: |

Type:

BEGA Product:

Project:


Modified:

Available options

- | | |
|---------------------------------|---------------------------------|
| ☐ CUS | Custom finish |
| ☐ DALI-2 | Enabled for DALI control system |
| ☐ FSC | Fusing |
| ☐ MGU | Marine grade undercoat |
| ☐ RAL | RAL Classic, matte finish |

Included (available for pre-shipment)

- | | |
|---------------------------------|--------------------------|
| ☐ B19538 | Small opening wiring box |
|---------------------------------|--------------------------|



Surface mounted downlight · Symmetric			
	LED	A	B
B66055	3.0W	3 ³ / ₄	3 ³ / ₄