

Application

Control up to 20 DALI-2 operating devices including luminaires or sensors. The Air Connector requires line voltage power input and receives a wired DALI-2 group connection. All configuration and control of this device communicates with the BEGA Connect Cloud via a Narrow Band IoT wireless connection.

Materials

- Marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy
- Composite housing
- Black connecting cable
- High temperature silicone gasket
- Mechanically captive stainless steel fasteners
- Stainless steel hardware
- Mounting hardware included

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 65

Weight: 4.0 lbs.

EPA (Effective projection area): 0.2 sq. ft.

Electrical

Operating voltage	120-277V AC
Minimum start temperature	-20° C
Controllability	DALI-2

Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL, custom, and premium colors provided in polyester powder and/or liquid paint.

Available colors

- ☐ Black (BLK)
- ☐ Bronze (BRZ)
- ☐ Silver (SLV)
- ☐ White (WHT)

Type:

BEGA Product:

Project:

Modified:



Air Connector · Pole mount

	A	B
B71297	4	9 ³ / ₈

