

Application

Factory sealed recessed wall luminaire with asymmetric floodlight optics, designed to be installed in walls or other vertical or horizontal surfaces for both interior and exterior locations.

Materials

- Clear safety glass with optical texture
- Corrosion-resistant 304 grade stainless steel
- Stainless steel screw clamps
- Aluminum installation housing
- Pure anodized aluminum reflector

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 67

Weight: 12.8lbs.

Electrical

- Operating voltage24VDC (remote power supply req.)
- Minimum start temperature-40° C
- LED module wattage9.7 W
- System wattage13.0 W
- ControllabilityNon-Dimming
- Color rendering indexRa > 80
- Luminaire lumens453 lm
- LED service life (L70)60000 hrs

LED color temperature

- ☐ 4000K (K4)
- ☐ 3500K (K35)
- ☐ 3000K (K3)
- ☐ 2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

#4 brushed stainless steel. Custom colors are not available.

Type:

BEGA Product:

Project:

Modified:

Available options

- ☐ FSC Fusing

Available accessories

- ☐ B19580 Remote driver box · Static white
- ☐ B19591 Remote driver box · Static white

See individual accessory spec sheet for details.

Included (available for pre-shipment)

- ☐ BB7002LED Installation housing



Recessed wall luminaire · Asymmetric · 24V DC				
	LED	A	B	C
B77002	9.7 W	39 ³ / ₈	2 ¹ / ₈	4

