

Application

Factory sealed recessed wall luminaire with symmetric floodlight optics, designed to be installed in walls or other vertical or horizontal surfaces for both interior and exterior locations.

Materials

- Clear safety glass with optical texture
- Corrosion-resistant 304 grade stainless steel
- Stainless steel screw clamps
- Aluminum installation housing
- Pure anodized aluminum reflector

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 67

Weight: 5.3 lbs.

Electrical

- | | |
|---------------------------|----------------------------------|
| Operating voltage | 24VDC (remote power supply req.) |
| Minimum start temperature | -40° C |
| LED module wattage | 3.7 W |
| System wattage | 5.0 W |
| Controllability | Non-Dimming |
| Color rendering index | Ra > 80 |
| Luminaire lumens | 250 lm |
| LED service life (L70) | 60000 hrs |

LED color temperature

- ☐ 4000K (K4)
- ☐ 3500K (K35)
- ☐ 3000K (K3)
- ☐ 2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

#4 brushed stainless steel. Custom colors are not available.

Type:

BEGA Product:

Project:

Modified:

Available accessories

- ☐ B19580 Remote driver box · Static white
- ☐ B19591 Remote driver box · Static white

See individual accessory spec sheet for details.

Included (available for pre-shipment)

- ☐ BB7001LED Installation housing



Recessed wall luminaire · Symmetric · 24V DC				
	LED	A	B	C
B77004	3.7 W	15 ³ / ₄	2 ¹ / ₈	3 ⁷ / ₈

BEGA 1000 BEGA Way, Carpinteria, CA 93013 (805) 684-0533 info@bega-us.com

Due to the dynamic nature of lighting products and the associated technologies, luminaire data on this sheet is subject to change at the discretion of BEGA North America. For the most current technical data, please refer to bega-us.com
© copyright BEGA 2026 Updated 04/03/26

