

Application

Flush in-grade small-scale location uplights. Designed for indicator or general area lighting. Luminaires require a remote 24 V DC class 2 power supply suitable to operate at the intended LED wattage.

Materials

Clear safety glass with white ceramic coating
Corrosion-resistant 304 grade stainless steel
High temperature silicone gasket
Mechanically captive stainless steel fasteners

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 68

Weight: 1.8 lbs.

Electrical

Operating voltage	24VDC (remote power supply req.)
Minimum start temperature	-40° C
LED module wattage	0.6W
System wattage	1.0W
Controllability	Non-Dimming
Color rendering index	Ra > 80
Luminaire lumens	28 lm
LED service life (L70)	60000 hrs

LED color temperature

4000K (K4)
3500K (K35)
3000K (K3)
2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

#4 brushed stainless steel. Custom colors are not available.

Type:

BEGA Product:


Project:

Modified:

Available accessories

B19580 Remote driver box · Static white
B19591 Remote driver box · Static white

See individual accessory spec sheet for details.



In-grade luminaire · Location Luminaire · 24V DC

	LED	A	B	C
B77027	0.6W	3	1 3/4	2 1/2

