

Application

Pole-top luminaire with unshielded symmetric light distribution. The symmetric distribution is ideal for illuminating squares, plazas and other open areas.

Materials

White UV-stabilized acrylic diffuser
Marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy
NRTL listed to North American Standards, suitable for wet locations
Protection class IP 65

Weight: 22.0lbs.

EPA (Effective projection area): 1.3 sq. ft.

Electrical

Operating voltage 120-277VAC
Minimum start temperature -30° C
LED module wattage 23.4 W
System wattage 27.0 W
Controllability 0-10V dimming down to 1%
Color rendering index Ra > 80
Luminaire lumens 2654 lm
LED service life (L70) 60000hrs

LED color temperature

4000K (K4)
3500K (K35)
3000K (K3)
2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL, custom, and premium colors provided in polyester powder and/or liquid paint.

Available colors

Black (BLK) Bronze (BRZ)
Silver (SLV) White (WHT)
RAL: CUS:

Type:


BEGA Product:

Project:

Modified:

Available options

CUS Custom finish
DALI-2 Enabled for DALI control system
FSC Fusing
MGU Marine grade undercoat
RAL RAL Classic, matte finish



Pole-top luminaire · Symmetric

	LED	A	B
B77120	23.4 W	25 ^{5/8}	23 ^{5/8}

