

Application

Pole top luminaire with symmetric distribution. An unshielded diffuser creates a soft, uniform distribution and visual interest for pedestrian environments.

Materials

White UV-stabilized acrylic diffuser
Marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy
High temperature silicone gasket
Integral surge protector

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 65

Weight: 11.9lbs.

EPA (Effective projection area): 1.6 sq. ft.

Electrical

Operating voltage	120-277VAC
Minimum start temperature	-30° C
LED module wattage	16.8W
System wattage	19.0W
Controllability	0-10V, TRIAC, and ELV dimmable
Color rendering index	Ra > 80
Luminaire lumens	1499lm
LED service life (L70)	60000hrs

LED color temperature

- ☐ 4000K (K4)
- ☐ 3500K (K35)
- ☐ 3000K (K3)
- ☐ 2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL, custom, and premium colors provided in polyester powder and/or liquid paint.

Available colors

- ☐ Black (BLK)
- ☐ Bronze (BRZ)
- ☐ Silver (SLV)
- ☐ White (WHT)
- ☐ RAL:
- ☐ CUS:

Type:


BEGA Product:

Project:

Modified:

Available options

- ☐ CUS
- Custom finish
- ☐ FSC
- Fusing
- ☐ MGU
- Marine grade undercoat
- ☐ RAL
- RAL Classic, matte finish



Edge-lit pole-top luminaire · Symmetric			
	LED	A	B
B77121	16.8W	15 ^{3⁄8}	19 ^{3⁄8}

