

Application

Pole top luminaire with symmetric light distribution. The edge-lit source ensures visual comfort, while the unique interreflection of light in the clear diffuser creates visual interest. Ideal for illuminating pedestrian spaces such as plazas and building entrances.

Materials

- Clear UV-stabilized acrylic diffuser
- Optically textured UV-stabilized acrylic diffuser
- Marine grade, copper free (≤ 0.3% copper content) A360.0 aluminum alloy
- High temperature silicone gasket
- Integral surge protector
- Pure anodized aluminum reflector

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 65

Weight: 13.2 lbs.

EPA (Effective projection area): 1.6 sq. ft.

Electrical

- Operating voltage120-277V AC
- Minimum start temperature-30° C
- LED module wattage24.0 W
- System wattage28.0 W
- Controllability0-10V dimming down to 1%
- Color rendering indexRa > 80
- Luminaire lumens2408 lm
- LED service life (L70)60000 hrs

LED color temperature

- 4000K (K4)
- 3500K (K35)
- 3000K (K3)
- 2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL, custom, and premium colors provided in polyester powder and/or liquid paint.

Available colors

- | | |
|--------------|--------------|
| Black (BLK) | Bronze (BRZ) |
| Silver (SLV) | White (WHT) |
| RAL: | CUS: |

Type:


BEGA Product:

Project:

Modified:

Available options

- | | |
|--------|---------------------------------|
| CUS | Custom finish |
| DALI-2 | Enabled for DALI control system |
| FSC | Fusing |
| MGU | Marine grade undercoat |
| RAL | RAL Classic, matte finish |



Edge-lit pole-top luminaire · Symmetric			
	LED	A	B
B77135	24.0 W	20 1⁄8	27 3⁄8

