

Application

Pole-top luminaire with shielded symmetric light distribution. The symmetric distribution is ideal for illuminating squares, plazas and other open areas.

Materials

Clear UV-stabilized acrylic diffuser
Marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 65

Weight: 22.0 lbs.

EPA (Effective projection area): 1.3 sq. ft.

Electrical

Operating voltage	120-277V AC
Minimum start temperature	-30° C
LED module wattage	23.4 W
System wattage	27.0 W
Controllability	0-10V dimming down to 1%
Color rendering index	Ra > 80
Luminaire lumens	1697 lm
LED service life (L70)	60000 hrs

LED color temperature

- 4000K (K4)
- 3500K (K35)
- 3000K (K3)
- 2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL, custom, and premium colors provided in polyester powder and/or liquid paint.

Available colors

Black (BLK)	Bronze (BRZ)
Silver (SLV)	White (WHT)
RAL:	CUS:

Type:


BEGA Product:

Project:

Modified:

Available options

CUS	Custom finish
DALI-2	Enabled for DALI control system
MGU	Marine grade undercoat
RAL	RAL Classic, matte finish



Pole-top luminaire · Symmetric

	LED	A	B
B77142	23.4 W	25 ^{5/8}	23 ^{5/8}

