

Application

Pole-top luminaire with symmetric light distribution. Ideal for illuminating squares, plazas and other open areas while adding visual interest.

Materials

Clear UV-stabilized acrylic diffuser  
Marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy  
High temperature silicone gasket  
Pure anodized aluminum reflector

NRTL listed to North American Standards, suitable for wet locations  
Protection class IP 65

Weight: 11.0 lbs.

EPA (Effective projection area): 1.1 sq. ft.

Electrical

Operating voltage 120-277V AC  
Minimum start temperature -30° C  
LED module wattage 31.0 W  
System wattage 36.0 W  
Controllability 0-10V dimming down to 1%  
Color rendering index Ra > 80  
Luminaire lumens 3370 lm  
LED service life (L70) 60000 hrs

LED color temperature

4000K (K4)  
3500K (K35)  
3000K (K3)  
2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL, custom, and premium colors provided in polyester powder and/or liquid paint.

Available colors

|              |              |
|--------------|--------------|
| Black (BLK)  | Bronze (BRZ) |
| Silver (SLV) | White (WHT)  |
| RAL:         | CUS:         |

Type:


BEGA Product:

Project:

Modified:

Available options

|        |                                 |
|--------|---------------------------------|
| CUS    | Custom finish                   |
| DALI-2 | Enabled for DALI control system |
| FSC    | Fusing                          |
| MGU    | Marine grade undercoat          |
| RAL    | RAL Classic, matte finish       |



Pole-top luminaire · Symmetric

|        | LED   | A                              | B                              |
|--------|-------|--------------------------------|--------------------------------|
| B77164 | 31.0W | 10 <sup>1</sup> / <sub>4</sub> | 25 <sup>3</sup> / <sub>4</sub> |

