

**Application**  
Pole-top luminaire with asymmetric wide beam light distribution. Ideal for illuminating perimeters of plazas, streets, and pathways while adding visual interest.

**Materials**  
Clear UV-stabilized acrylic diffuser  
Marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy  
High temperature silicone gasket  
Pure anodized aluminum reflector

**NRTL** listed to North American Standards, suitable for wet locations  
Protection class IP 65

**Weight:** 11.0lbs.

**EPA (Effective projection area):** 1.1 sq. ft.

**Electrical**  
Operating voltage 120-277VAC  
Minimum start temperature -30° C  
LED module wattage 31.0W  
System wattage 36.0W  
Controllability 0-10V dimming down to 1%  
Color rendering index Ra > 80  
Luminaire lumens 3134 lm  
LED service life (L70) 60000hrs

**LED color temperature**

- ☐ 4000K (K4)
- ☐ 3500K (K35)
- ☐ 3000K (K3)
- ☐ 2700K (K27)

**BEGA** can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

**Finish**


All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL, custom, and premium colors provided in polyester powder and/or liquid paint.

**Available colors**

- ☐ Black (BLK)
- ☐ Bronze (BRZ)
- ☐ Silver (SLV)
- ☐ White (WHT)
- ☐ RAL:
- ☐ CUS:

Type:  
BEGA Product:  
Project:  
Modified:

- Available options**
- ☐ CUS Custom finish
- ☐ DALI-2 Enabled for DALI control system
- ☐ FSC Fusing
- ☐ MGU Marine grade undercoat
- ☐ RAL RAL Classic, matte finish



| Pole-top luminaire · Asymmetric wide beam |       |               |
|-------------------------------------------|-------|---------------|
|                                           | LED   | A B           |
| B77165                                    | 31.0W | 10 1/4 25 3/4 |

