Type:
BEGA Product:
Project:
Modified:

Application
Pathway luminaire with shielded light for use in the private sector. These luminaires are ideally suited for gardens, entryways, and for many applications on paths and terraces. Hardscape base is intended for installation on foundations or paved surfaces. Low voltage magnetic transformer required for operation.

Materials
Clear safety glass with matte finish
Aluminum housing
High temperature silicone gasket
Galvanized steel anchorage

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 65

Weight: 6.3 lbs.

Electrical

Operating voltage	12VAC
Minimum start temperature	-40° C
LED module wattage	2.1 W
System wattage	3.4 W
Controllability	Non-Dimming
Color rendering index	Ra > 90
Luminaire lumens	136 lm
LED service life (L70)	60000 hrs

LED color temperature
☐ 4000K (K4)
☐ 3500K (K35)
☐ 3000K (K3)
☐ 2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish
All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL, custom, and premium colors provided in polyester powder and/or liquid paint.

Available colors
☐ Black (BLK)
☐ Silver (SLV)
☐ Natural Bronze (NTB)
☐ CUS:
☐ Bronze (BRZ)
☐ White (WHT)
☐ RAL:


Available options

☐ CUS	Custom finish
☐ MGU	Marine grade undercoat
☐ NTB	Natural bronze (premium finish)
☐ RAL	RAL Classic, matte finish

Available accessories

☐ B536	Low voltage magnetic transformer · 300W

See individual accessory spec sheet for details.





Garden bollard · Hardscape base · 12V AC

	LED	A	B	C	D
B77238	2.1 W	3 1/2	27 1/2	4 1/8	2 1/2

BEGA 1000 BEGA Way, Carpinteria, CA 93013 (805) 684-0533 info@bega-us.com

Due to the dynamic nature of lighting products and the associated technologies, luminaire data on this sheet is subject to change at the discretion of BEGA North America. For the most current technical data, please refer to bega-us.com
© copyright BEGA 2026