

Application

Compact rectangular floodlight with mounting canopy and outrigger arm. Designed to illuminate architecture and signage. Pair with a variety of optical accessories.

Materials

- Clear safety glass with optical texture
- Marine grade, copper free (≤ 0.3% copper content) A360.0 aluminum alloy
- High temperature silicone gasket
- 304 stainless steel outrigger arm
- Pure anodized aluminum reflector

NRTL listed to North American Standards, suitable for wet locations  
Protection class IP 65

Weight: 5.3 lbs.

EPA (Effective projection area): 0.5 sq. ft.

Electrical

- Operating voltage120, 220-240 OR 277 VAC
- Minimum start temperature-30° C
- LED module wattage17.9 W
- System wattage20.4 W
- Controllability0-10V dimmable
- Color rendering indexRa > 80
- Luminaire lumens2456 lm
- LED service life (L70)60000 hrs

LED color temperature

- 4000K (K4)
- 3500K (K35)
- 3000K (K3)
- 2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL, custom, and premium colors provided in polyester powder and/or liquid paint.

Available colors

- Black (BLK)
- Silver (SLV)
- Natural Bronze (NTB)
- CUS:
- Bronze (BRZ)
- White (WHT)
- RAL:

Type:


BEGA Product:

Project:

Modified:

Available options

- B548Barn door shield
- B70500Glare shield · 180°
- CUSCustom finish
- FSCFusing
- MGUMarine grade undercoat
- NTBNatural bronze (premium finish)
- RALRAL Classic, matte finish



| Floodlight · Wide beam |        |         |       |        |   |       |
|------------------------|--------|---------|-------|--------|---|-------|
|                        | LED    | β       | A     | B      | C | D     |
| B77552                 | 17.9 W | 74°x89° | 6 1/2 | 27 5/8 | 2 | 7 1/2 |