

Application

Compact floodlight with mounting canopy for direct mounting to horizontal or vertical surfaces. Designed to illuminate architectural features, signage, landscaping, or to provide general illumination in a space. Pair with a variety of optical accessories.

Materials

- Clear safety glass
- Marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy
- High temperature silicone gasket
- Mechanically captive stainless steel fasteners
- Pure anodized aluminum reflector
- Silicone optic with excellent high temperature and UV stability

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 65

Weight: 2.0 lbs.

Electrical

- Operating voltage24VDC (remote power supply req.)
- Minimum start temperature-40° C
- LED module wattage7.9W
- System wattage9.0W
- ControllabilityNon-Dimming
- Color rendering indexRa > 80
- Luminaire lumens888lm
- LED service life (L70)60000 hrs

LED color temperature

- 4000K (K4)
- 3500K (K35)
- 3000K (K3)
- 2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL, custom, and premium colors provided in polyester powder and/or liquid paint.

Available colors

- Black (BLK)
- White (WHT)
- Silver (SLV)
- CUS:
- Bronze (BRZ)
- Natural Bronze (NTB)
- RAL:

Type:

BEGA Product:

Project:

Modified:

Available options

- AMBAmber LED
- B70050Elliptical spread lens
- B70755Glare shield · 180°
- CUSCustom finish
- MGUMarine grade undercoat
- NTBNatural bronze (premium finish)
- RALRAL Classic, matte finish


Available accessories

- B19580Remote driver box · Static white
- B19591Remote driver box · Static white

See individual accessory spec sheet for details.

Included (available for pre-shipment)

- B19538Small opening wiring box



Compact floodlight · Wide beam · 24V DC						
	LED	β	A	B	C	D
B77607	7.9W	47°	4 1⁄8	5 7⁄8	4 3⁄8	3 1⁄2

