

Application

Compact floodlight with mounting canopy for direct mounting to horizontal or vertical surfaces. Designed to illuminate architectural features, signage, landscaping, or to provide general illumination in a space. Pair with a variety of optical accessories.

Materials

- Clear safety glass
- Marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy
- High temperature silicone gasket
- Mechanically captive stainless steel fasteners
- Pure anodized aluminum reflector
- Silicone optic with excellent high temperature and UV stability

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 65

Weight: 4.4 lbs.

Electrical

- Operating voltage120-277V AC
- Minimum start temperature-30° C
- LED module wattage48.2 W
- System wattage51.0 W
- Controllability0-10V dimmable
- Color rendering indexRa > 90
- Luminaire lumens4231 lm
- LED service life (L70)60000 hrs

LED color temperature

- ☐ 4000K (K4)
- ☐ 3500K (K35)
- ☐ 3000K (K3)
- ☐ 2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL, custom, and premium colors provided in polyester powder and/or liquid paint.

Available colors

- ☐ Black (BLK)
- ☐ Silver (SLV)
- ☐ Natural Bronze (NTB)
- ☐ CUS:
- ☐ Bronze (BRZ)
- ☐ White (WHT)
- ☐ RAL:

Type:


BEGA Product:

Project:

Modified:

Available options

- ☐ B70065Elliptical spread lens
- ☐ B70721Glare shield · 360°
- ☐ B70758Glare shield · 180°
- ☐ B70775Concentric ring louver
- ☐ CUSCustom finish
- ☐ DALI-2Enabled for DALI control system
- ☐ FSCFusing
- ☐ MGUMarine grade undercoat
- ☐ NTBNatural bronze (premium finish)
- ☐ RALRAL Classic, matte finish



Compact floodlight · Narrow beam

	LED	β	A	B	C	D
B77659	48.2 W	22°	9 1/8	12	8 5/8	5 1/8

