

Application

Compact floodlight with mounting canopy and outrigger arm. Designed to illuminate architectural features and signage. Pair with a variety of optical accessories.

Materials

- Clear safety glass
- Marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy
- Mechanically captive stainless steel fasteners
- High temperature silicone gasket
- 304 stainless steel outrigger arm
- Pure anodized aluminum reflector

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 65

Weight: 7.5 lbs.

EPA (Effective projection area): 0.6 sq. ft.

Electrical

- Operating voltage120-277VAC
- Minimum start temperature-30° C
- LED module wattage17.7 W
- System wattage21.0 W
- Controllability0-10V, TRIAC, and ELV dimmable
- Color rendering indexRa > 80
- Luminaire lumens2135 lm
- LED service life (L70)60000 hrs

LED color temperature

- ☐ 4000K (K4)
- ☐ 3500K (K35)
- ☐ 3000K (K3)
- ☐ 2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL, custom, and premium colors provided in polyester powder and/or liquid paint.

Available colors

- ☐ Black (BLK)
 - ☐ Silver (SLV)
 - ☐ Natural Bronze (NTB)
 - ☐ CUS:
- ☐ Bronze (BRZ)
 - ☐ White (WHT)
 - ☐ RAL:

Type:


BEGA Product:

Project:

Modified:

Available options

- ☐ B70060
 - ☐ B70757
 - ☐ CUS
 - ☐ FSC
 - ☐ MGU
 - ☐ NTB
 - ☐ RAL
- Elliptical spread lens
 - Glare shield · 180°
 - Custom finish
 - Fusing
 - Marine grade undercoat
 - Natural bronze (premium finish)
 - RAL Classic, matte finish



Compact floodlight · Wide beam						
	LED	β	A	B	C	D
B77665	17.7 W	47°	6 1/4	27 1/2	6 1/2	7 1/2