

Application

Ground mounted luminaire for illuminating horizontal surfaces from low mounting heights. This luminaire is ideally suited for providing spatial illumination in squares, entrances and wide pathways in private and public areas. Provided with mounting system that allows the luminaire to be adjusted independent of anchor bolt orientation.

Materials

Clear safety glass
Marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy
Self-expanding sleeve anchors for pre-cast concrete
Pure anodized aluminum reflector

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 65

Weight: 9.7 lbs.

Electrical

Operating voltage 120-277VAC
Minimum start temperature -30° C
LED module wattage 12.3W
System wattage 16.0W
Controllability 0-10V dimmable
Color rendering index Ra > 80
Luminaire lumens 648lm
LED service life (L70) 60000hrs

LED color temperature

- 4000K (K4)
- 3500K (K35)
- 3000K (K3)
- 2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL, custom, and premium colors provided in polyester powder and/or liquid paint.

Available colors

- Black (BLK)
- Silver (SLV)
- RAL:
- Bronze (BRZ)
- White (WHT)
- CUS:

Type:


BEGA Product:

Project:

Modified:

Available options

- 70894 Direct burial anchorage (replaces included anchorage kit, pre-shippable)
- AMB Amber LED
- CUS Custom finish
- MGU Marine grade undercoat
- RAL RAL Classic, matte finish



On-ground luminaire · Wide beam					
	LED	A	B	C	D
B77735	12.3W	7 ⁷ / ₈	8 ¹ / ₄	2 ³ / ₈	4 ⁷ / ₈

