

Application

Bollard luminaire with unshielded 360° light distribution. Provided without safety guard and three-ply opal glass for even illumination. Designed for use in the illumination of gardens and residential installations.

Materials

Hand-blown three-ply opal glass
Marine grade, copper free (≤0.3% copper content) A360.0 aluminum alloy

NRTL listed to North American Standards, suitable for wet locations
Protection class IP 65

Weight: 5.7 lbs.

Electrical

Operating voltage	120-277VAC
Minimum start temperature	-30° C
Maximum ambient temperature	90° C
LED module wattage	3.9W
System wattage	10.0W
Controllability	0-10V dimmable
Color rendering index	Ra > 90
Luminaire lumens	441 lm
LED service life (L70)	60000 hrs

LED color temperature

- ☐ 4000K (K4)
- ☐ 3500K (K35)
- ☐ 3000K (K3)
- ☐ 2700K (K27)

BEGA can supply you with suitable LED replacement modules for up to 20 years after the purchase of LED luminaires - see website for details

Finish

All BEGA standard finishes are matte, textured powder coat with minimum 3 mil thickness. BEGA Unidure® finish provides superior fade protection in Black, Bronze, and Silver. BEGA standard White is a super durable polyester powder. Optionally available RAL, custom, and premium colors provided in polyester powder and/or liquid paint.

Available colors

- | | |
|---|---------------------------------------|
| ☐ Black (BLK) | ☐ Bronze (BRZ) |
| ☐ Silver (SLV) | ☐ White (WHT) |
| ☐ Natural Bronze (NTB) | ☐ RAL: |
| ☐ CUS: | |

Type:

BEGA Product:

Project:

Modified:

Available options

- | | |
|------------------------------|---------------------------|
| ☐ CUS | Custom finish |
| ☐ FSC | Fusing |
| ☐ MGU | Marine grade undercoat |
| ☐ RAL | RAL Classic, matte finish |



Bollard · Unshielded

	LED	A	B
B77742	3.9W	4 ³ / ₈	28 ³ / ₄

